

Table 4-1. Fuel System Specifications

FUEL SYSTEM	TYPE
Intake (XB9)	45 mm downdraft manifold, ram air
Intake (XB12)	49 mm downdraft manifold, ram air
Fuel delivery	DDFI fuel injection
Fuel pressure	46-53 Psi (317-365 kPa)
Recommended fuel	91 Octane

Table 4-2. Fuel Tank Specifications

FUEL TANK CAPACITY	GALLONS	LITERS
Total (including reserve)	3.7	14.0
Reserve/Low fuel indicator at	0.7	2.7

Table 4-3. Idle Speed Specifications

ADJUSTMENT	RPM
Normal idle speed	1050 -1150 RPM

Torque Values

ITEM	TORQUE		NOTES
Airbox back plate fasteners	84-120 in-lbs	9.5-13.6 Nm	page 4-132
Bank angle sensor mounting fastener	12-36 in-lbs	1.4-4.1 Nm	page 4-103
Battery terminal hardware	60-96 in-lbs	7-11 Nm	page 4-121
Cooling fan fasteners	12-36 in-lbs	1.4-4.1 Nm	page 4-106
Engine temperature sensor	120-168 in-lbs	13.6-19 Nm	page 4-102
Fuel cap retaining ring fasteners	17-70 in-lbs	1.9-7.9 Nm	page 4-122
Fuel pump drain plug	84-108 in-lbs	9.5-12.2 Nm	page 4-107
Fuel pump drain plug	84-108 in-lbs	9.5-12.2 Nm	page 4-113
Fuel pump harness fastener	18-22 in-lbs	2.0-2.5 Nm	page 4-111
Fuel pump harness fastener	18-22 in-lbs	2.0-2.5 Nm	page 4-119
Fuel pump screws	48-51 in-lbs	5.4-5.8 Nm	page 4-112
Fuel pump screws	48-51 in-lbs	5.4-5.8 Nm	page 4-120
Fuel pump wire harness fastener	18-22 in-lbs	2.0-2.5 Nm	page 4-111
Fuel pump wire harness fastener	18-22 in-lbs	2.0-2.5 Nm	page 4-119
Fuel rail fasteners	24-28 in-lbs	2.7-3.2 Nm	LOCTITE 222 (purple), page 4-126
Fuel supply line banjo fitting	84-108 in-lbs	9.5-12.2 Nm	page 4-112
Fuel supply line banjo fitting	84-108 in-lbs	9.5-12.2 Nm	page 4-120
Fuel tank vent valve fasteners	39-41 in-lbs	4.4-4.6 Nm	page 4-121
Ignition coil mounting screws	120-144 in-lbs	13.6-16.3 Nm	page 4-100
Ignition rotor mounting bolt	43-53 in-lbs	5-6 Nm	LOCTITE 243 (blue), page 4-98
Inner timer cover screws	12-20 in-lbs	1.3-2.3 Nm	page 4-98

ITEM	TORQUE		NOTES
Intake flange screws	96-120 in-lbs	10.8-13.6 Nm	page 4-127
Oxygen sensor	40-45 ft-lbs	54-61 Nm	LOCTITE ANTI-SEIZE, page 4-101
Throttle position sensor	16-20 in-lbs	1.8-2.3 Nm	LOCTITE 222 (purple), page 4-105
Timer plate studs	15-30 in-lbs	2-3 Nm	page 4-98
Upper tie bar	25-27 ft-lbs	33.9-36.6 Nm	page 4-102